

(19) World Intellectual Property Organization  
International Bureau



(43) International Publication Date  
27 June 2002 (27.06.2002)

PCT

(10) International Publication Number  
**WO 02/50213 A2**

(51) International Patent Classification<sup>7</sup>: **C10G 65/12**

Badhuisweg 3, NL-1031 CM Amsterdam (NL). **POLDER, Kevin, John, Anthony** [NL/FR]; Route Départementale no. 3, F-76650 Petit Couronne (FR).

(21) International Application Number: PCT/EP01/15134

(22) International Filing Date:  
18 December 2001 (18.12.2001)

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZM, ZW.

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
00403588.7 19 December 2000 (19.12.2000) EP

(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

(71) Applicant (*for all designated States except US*): **SHELL INTERNATIONALE RESEARCH MAATSCHAPPIJ B.V.** [NL/NL]; Carel van Bylandtlaan 30, NL-2596 HR The Hague (NL).

(72) Inventors; and



(75) Inventors/Applicants (*for US only*): **VAN BEIJNUM, Johannes** [NL/NL]; Badhuisweg 3, NL-1031 CM Amsterdam (NL). **GEUKEMA, Arjen, Peter** [NL/NL];

Published:

— *without international search report and to be republished upon receipt of that report*

[Continued on next page]

(54) Title: PROCESS TO PREPARE A SPINDLE OIL, LIGHT MACHINE OIL AND A MEDIUM MACHINE OIL BASE OIL GRADE FROM THE BOTTOMS FRACTION OF A FUELS HYDROCRACKING PROCESS



(57) Abstract: Process to prepare a spindle oil, light machine oil and a medium machine oil base oil grade by (a) performing a separate catalytic dewaxing on a spindle oil fraction, a light machine oil fraction and a medium machine oil fraction as obtained in a vacuum distillation of a bottoms fraction of a fuels hydrocracking process; (b) performing a separate hydrofinishing of the light and medium machine oil fractions obtained in step (a); (c) separating the low boiling compounds from the spindle oil, light machine oil and medium machine oil fractions as obtained in step (a) and (b) and obtaining the spindle oil, light machine oil and medium machine oil base oil grade; (e) wherein the vacuum distillation is performed by alternatingly performing the distillation in two modes wherein the first mode (d1) the bottoms fraction is separated into a gas oil fraction, a spindle oil fraction, a medium machine oil fraction and a first rest fraction boiling between said spindle oil and medium machine oil fraction and in the second mode (d2) the bottoms fraction is separated into a gas oil fraction, a spindle oil fraction, a light machine oil fraction and a second rest fraction boiling above the light machine oil fraction.



*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

PROCESS TO PREPARE A SPINDLE OIL, LIGHT MACHINE OIL AND A  
MEDIUM MACHINE OIL BASE OIL GRADE FROM THE BOTTOMS  
FRACTION OF A FUELS HYDROCRACKING PROCESS

The invention is directed to a process to prepare a spindle oil, light machine oil and a medium machine oil base oil grade from the bottoms fraction of a fuels hydrocracking process.

5        Such a process is known from EP-A-699225. This publication discloses a process to prepare two base oil grades, a so-called 100N and 150N grade. The heavier 150N grade typically has a viscosity at 100 °C of between 5.5 cSt and 6 cSt according to this publication. In this  
10       process the fuels hydrocracker bottom fraction, further also referred to as hydrowax, is fractionated in a vacuum distillation into various fractions comprising the two desired base oil fractions. The base oil fractions are subsequently further processed, by dewaxing and  
15       stabilisation, to the desired base oil grade and the remaining fractions are recycled to the fuels hydrocracker. The one through conversion of the fuels hydrocracker is described to be about 60% which results in a low fuel yield in the fuels hydrocracker.

20       WO-A-9718278 discloses a process, comparable to the process of above cited EP-A-699225, wherein up to 4 base oil grades, e.g. a 60N, 100N and 150N, are prepared starting from hydrowax. In this process hydrowax is fractionated in a vacuum distillation into 5 fractions of  
25       which the heavier 4 fractions are further processed to different base oil grades by first performing a catalytic dewaxing followed by a hydrofinishing step.

In an article of Hennico, A., Billon, A., Bigeard, P.H., Peries, J.P., "IFP's New Flexible

Hydrocracking Process...", Revue de l'institut Francais  
du Pétrole, Vol. 48, No. 2, Mars-Avril, a fuels  
hydrocracking process is described wherein several  
products are obtained ranging from fuels to three base  
5 oils qualities, namely of the 100N-, 200N- and 350N-type.

In view of the above processes there is room for  
improving the overall yield of base oil products as  
calculated on the hydrocracker bottoms.

The following process aims at improving this yield of  
10 base oil grades as calculated on the hydrocracker  
bottoms. Process to prepare a spindle oil, light machine  
oil and a medium machine oil base oil grade by  
(a) performing a separate catalytic dewaxing on a spindle  
oil fraction, a light machine oil fraction and a medium  
15 machine oil fraction as obtained in a vacuum distillation  
of a bottoms fraction of a fuels hydrocracking process;  
(b) performing a separate hydrofinishing of the light and  
medium machine oil fractions obtained in step (a);  
(c) separating the low boiling compounds from the spindle  
20 oil, light machine oil and medium machine oil fractions  
as obtained in step (a) and (b) and obtaining the spindle  
oil, light machine oil and medium machine oil base oil  
grade;  
(d) wherein the vacuum distillation is performed by  
25 alternately performing the distillation in two modes  
wherein the first mode (d1) the bottoms fraction is  
separated into one or more gas oil fractions, a spindle  
oil fraction, a medium machine oil fraction and a first  
rest fraction boiling between said spindle oil and medium  
30 machine oil fraction and in the second mode (d2) the  
bottoms fraction is separated into one or more gas oil  
fractions, a spindle oil fraction, a light machine oil  
fraction and a second rest fraction boiling above the  
light machine oil fraction.

It has been found that by the above process more than two grades of high quality base oils can be prepared in a high yield on hydrowax. The required base oil properties for the different grades such as viscosity, flash point and/or Noack volatility are easily met by performing the distillation in the two dedicated modes according to the process of the present invention.

In the context of the present invention terms as spindle oil, light machine oil and medium machine oil will refer to base oil grades having an increasing kinematic viscosity at 100 °C and wherein the spindle oil additionally has a maximum volatility specification. The advantages of the present process are achieved for any group of base oils having such different viscosity requirement and volatility specification. Preferably a spindle oil is a light base oil product having a kinematic viscosity at 100 °C of below 5.5 cSt and preferably above 3.5. The spindle oil can have either a Noack volatility, as determined by the CEC L-40-T87 method, of preferably below 20% and more preferably below 18% or a flash point, as measured according to ASTM D93, of above 180 °C. Preferably the light machine oil has a kinematic viscosity at 100 °C of below 9 cSt and preferably above 6.5 cSt and more preferably between 8 and 9 cSt. Preferably the medium machine oil has a kinematic viscosity at 100 °C of below 13 cSt and preferably above 10 cSt and more preferably between 11 and 12.5 cSt. The corresponding base oil grade can have a viscosity index of between 95 and 120.

Terms as spindle oil fraction, light machine oil fraction and medium machine oil fraction refer to the distillate fraction as obtained in the vacuum distillation and from which the corresponding base oil grades are prepared.

With a fuels hydrocracker in the context of the present invention is meant a hydrocracker process which main products are naphtha, kerosene and gas oil. The conversion, expressed in the weight percentage of the fraction in the feed which boils above 370 °C which are converted to products boiling below 370 °C, in the hydrocracker process is typically above 50 wt%. This in contrast to a dedicated base oil hydrocracker which main products are base oil fractions and which process operates at a feed conversion of below 50 wt% and more typically between 20 and 40 wt%. Examples of possible fuels hydrocracker processes, which may yield a bottoms fraction which can be used in the present process, are described in the above referred to EP-A-699225, EP-A-649896, WO-A-9718278, EP-A-705321, EP-A-994173 and US-A-4851109.

Preferably the fuels hydrocracker is operated in two steps, consisting of a preliminary hydrotreating step followed by a hydrocracking step. In the hydrotreating step nitrogen and sulphur are removed and aromatics are saturated to naphthenes. The hydrowax and the resulting base oil grades will thus as a consequence have a very low content of sulphur, typically below 100 ppmw, and a very low content of nitrogen, typically below 10 ppmw.

In order to improve the yield of medium machine oil grade on hydrowax the fuels hydrocracker is more preferably operated by first (i) hydrotreating a hydrocarbon feed at a feed conversion, wherein the conversion, as defined above, of less than 30 wt% and preferably between 15 and 25 wt%, and (ii) hydrocracking the product of step (i) in the presence of a hydrocracking catalyst at such a conversion level that the overall conversion of step (i) and (ii) is between 55 and 80 wt% and preferably between 60 and 75 wt%.

It has been found that by performing the combined hydrotreating and hydrocracking step as described above a hydrowax is obtained which yields a high quantity of medium machine oil grade and of acceptable quality with respect to viscosity index. In addition a sufficient quantity of naphtha, kerosine and gas oils are obtained by this process. Thus a fuels hydrocracker process is obtained wherein simultaneously products ranging from naphtha to gas oil and a hydrowax is obtained, which hydrowax has the potential to yield a medium machine oil base oil grade. The viscosity index of the resulting base oil grades is suitably between 95 and 120, which is acceptable to yield base oils having a viscosity index according to the API Group II specifications. It has been found that the wt% of medium machine oil fraction, which fraction has a kinematic viscosity at 100 °C of above 9, in the 370 °C plus fraction of the hydrowax can be more than 15 wt% and more especially more than 25 wt% if the hydrocracker is operated as described above.

It has been found that in the hydrotreating step (i) the viscosity index of the hydrowax and the resulting base oil grades increases with the conversion in said hydrotreating step. By operating the hydrotreating step at high conversion levels of more than 30 wt% viscosity index values for the resulting base oils of well above 120 can be achieved. A disadvantage of such a high conversion in step (i) is however that the yield of medium machine oil fraction will be undesirably low. By performing step (i) at the above described conversion levels an API Group II medium machine oil grade base oil can be obtained in a desired quantity. The minimum conversion in step (i) will be determined by the desired viscosity index, of between 95 and 120, of the resulting base oil grades and the maximum conversion in step (i) is

determined by the minimum acceptable yield of medium machine oil grade.

5 The preliminary hydrotreating step is typically performed using catalyst and conditions as for example described in the above-mentioned publications related to hydrocracking. Suitable hydrotreating catalysts generally comprise a metal hydrogenation component, suitably Group IVB or VIII metal, for example cobalt-molybdenum, nickel-molybdenum, on a porous support, for example  
10 silica-alumina or alumina. The hydrotreating catalysts suitably contains no zeolite material or a very low content of less than 1 wt%. Examples of suitable hydrotreating catalysts are the commercial ICR 106, ICR 120 of Chevron Research and Technology Co.; 244, 411, DN-120, DN-180, DN-190 and DN-200 of Criterion Catalyst  
15 Co.; TK-555 and TK-565 of Haldor Topsoe A/S; HC-k, HC-P, HC-R and HC-T of UOP; KF-742, KF-752, KF-846, KF-848 STARS and KF-849 of AKZO Nobel/Nippon Ketjen; and HR-438/448 of Procatalyse SA.

20 The hydrocracking step is preferably a catalyst comprising an acidic large pore size zeolite within a porous support material with an added metal hydrogenation/dehydrogenation function. The metal having the hydrogenation/dehydrogenation function is preferably a  
25 Group VIII/Group VIB metal combination, for example nickel-molybdenum and nickel-tungsten. The support is preferably a porous support, for example silica-alumina and alumina. It has been found that a minimum amount of zeolite is advantageously present in the catalyst in  
30 order to obtain a high yield of medium machine oil fraction in the hydrowax when performing the hydrocracker at the preferred conversion levels as explained above. Preferably more than 1 wt% of zeolite is present in the catalyst. Examples of suitable zeolites are zeolite X, Y,  
35 ZSM-3, ZSM-18, ZSM-20 and zeolite beta of which zeolite Y



is most preferred. Examples of suitable hydrocracking catalysts are the commercial ICR 220 and ICR 142 of Chevron Research and Technology Co; Z-763, Z-863, Z-753, Z-703, Z-803, Z-733, Z-723, Z-673, Z-603 and Z-623 of Zeolist International; TK-931 of Haldor Topsoe A/S; DHC-32, DHC-41, HC-24, HC-26, HC-34 and HC-43 of UOP; KC2600/1, KC2602, KC2610, KC2702 and KC2710 of AKZO Nobel/Nippon Ketjen; and HYC 642 and HYC 652 of Procatalyse SA.

The feed to the preliminary hydrotreater can be for example a vacuum gas oil, light cycle oil obtained in a fluid catalytic cracking process or a deasphalted oil or mixtures of such feeds. In order to be able to prepare the desired quantity of medium machine oil grade a relatively heavy feed to the hydrocracking step is desired. Preferably a feed is used wherein more than 10 wt%, preferably more than 20 wt% and most preferably more than 30 wt% of the compounds present in said feed boil above 470 °C. Suitably less than 60 wt% of the compounds present in the feed boil above 470 °C.

The effluent of the hydrocracker is separated into one or more of the above referred to fuels fractions and a hydrowax containing residue. The hydrowax containing residue, wherein the hydrowax boils predominately above 370 °C, is used as feed of the vacuum distillation of step (d). With boiling predominately above 370 °C is especially meant that more than 95 wt% boils above 370 °C. The cut point between hydrowax and fuels fraction is not critical for the base oil preparation, because any lower boiling compounds present in the hydrowax containing residue will be removed from the base oil fractions in the vacuum distillation step (d).

The vacuum distillation step (d) can be operated as any conventional vacuum distillation which is suited to separate a hydrocarbon feed boiling mainly above 350 °C

under atmospheric conditions into different fractions. Typical pressures in the bottom of the vacuum distillation are between 80 and 110 mmHg. The cutting temperatures to obtain the different fractions will  
5 depend on the mode of distillation and the viscosity specification of the desired fractions for that distillation mode. By measuring the viscosity's of the obtained fractions and preferably also the Noack volatility for the spindle oil fraction one skilled in  
10 the art can easily determine the optimal vacuum distillation conditions. The rest fractions obtained in the vacuum distillation can optionally be recycled to the hydrocracker. Preferably this rest fraction is blended into the feed of a fluid catalytic cracker or steam  
15 cracker.

The catalytic dewaxing step and the hydrofinishing step and any further processing steps are preferably performed in a so-called blocked out operation, wherein, in a preferably continuous process, one base oil grade is  
20 prepared at a time. In this manner use can be made of the same apparatuses for the different base oils grades. In such a blocked out process the fractions obtained in the vacuum distillation are stored in for example storage tanks before being sequentially further processed in  
25 steps (a)-(c).

The catalytic dewaxing step can be performed by any process wherein in the presence of a catalyst and hydrogen the pour point of the base oil fraction is reduced. Suitably the pour point is reduced by at least  
30 10 °C and more suitably by at least 20 °C. Suitable dewaxing catalysts are heterogeneous catalysts comprising a molecular sieve and optionally in combination with a metal having a hydrogenation function, such as the Group VIII metals. Molecular sieves, and more suitably  
35 intermediate pore size zeolites, have shown a good

catalytic ability to reduce the pour point of a base oil fraction under catalytic dewaxing conditions. Preferably the intermediate pore size zeolites have a pore diameter of between 0.35 and 0.8 nm. Suitable intermediate pore size zeolites are ZSM-5, ZSM-12, ZSM-22, ZSM-23, SSZ-32, ZSM-35 and ZSM-48. Another preferred group of molecular sieves are the silica-aluminophosphate (SAPO) materials of which SAPO-11 is most preferred as for example described in US-A-4859311. ZSM-5 may optionally be used in its HZSM-5 form in the absence of any Group VIII metal. The other molecular sieves are preferably used in combination with an added Group VIII metal. Suitable Group VIII metals are nickel, cobalt, platinum and palladium. Examples of possible combinations are Ni/ZSM-5, Pt/ZSM-23, Pd/ZSM-23, Pt/ZSM-48 and Pt/SAPO-11. Further details and examples of suitable molecular sieves and dewaxing conditions are for example described in WO-A-9718278, US-A-5053373, US-A-5252527 and US-A-4574043.

The dewaxing catalyst suitably also comprises a binder. The binder can be a synthetic or naturally occurring (inorganic) substance, for example clay, silica and/or metal oxides. Natural occurring clays are for example of the montmorillonite and kaolin families. The binder is preferably a porous binder material, for example a refractory oxide of which examples are: alumina, silica-alumina, silica-magnesia, silica-zirconia, silica-thoria, silica-beryllia, silica-titania as well as ternary compositions for example silica-alumina-thoria, silica-alumina-zirconia, silica-alumina-magnesia and silica-magnesia-zirconia. More preferably a low acidity refractory oxide binder material which is essentially free of alumina is used. Examples of these binder materials are as silica, zirconia, titanium dioxide, germanium dioxide, boria and mixtures of two or

more of these of which examples are listed above. The most preferred binder is silica.

A preferred class of dewaxing catalysts comprise intermediate zeolite crystallites as described above and  
5 a low acidity refractory oxide binder material which is essentially free of alumina as described above, wherein the surface of the aluminosilicate zeolite crystallites has been modified by subjecting the aluminosilicate zeolite crystallites to a surface dealumination treat-  
10 ment. A preferred dealumination treatment is by contacting an extrudate of the binder and the zeolite with an aqueous solution of a fluorosilicate salt as described in for example US-A-5157191. Examples of suitable dewaxing catalysts as described above a silica  
15 bound and dealuminated Pt/ZSM-5 and silica bound and dealuminated Pt/ZSM-23, silica bound and dealuminated Pt/ZSM-12 and silica bound and dealuminated Pt/ZSM-22, as for example described in WO-A-200029511 and EP-B-832171.

20 Catalytic dewaxing conditions are known in the art and typically involve operating temperatures in the range of from 200 to 500 °C, suitably from 250 to 400 °C, hydrogen pressures in the range of from 10 to 200 bar, weight hourly space velocities (WHSV) in the range of  
25 from 0.1 to 10 kg of oil per litre of catalyst per hour (kg/l/hr), suitably from 0.2 to 5 kg/l/hr, more suitably from 0.5 to 3 kg/l/hr and hydrogen to oil ratios in the range of from 100 to 2,000 litres of hydrogen per litre of oil. If the dewaxing step and the hydrofinishing step  
30 are performed in cascade the pressure level in both steps is suitably of the same order. Because higher pressures are preferred in the hydrofinishing step in order to obtain a base oil having the desired properties the dewaxing step is suitably also performed at these higher  
35 pressures, even though a more selective dewaxing could

have been achieved at lower pressures. If no hydro-finishing step is required, as has been found to be the case when preparing the spindle oil base oil grade, a lower catalytic dewaxing pressure can be advantageously be applied. Suitable pressures are from 15 to 100 bar and more suitably from 15 to 65 bar.

The hydrofinishing step is to improve the quality of the dewaxed fraction. In this step lube range olefins are saturated, heteroatoms and colour bodies are removed and if the pressure is high enough residual aromatics are saturated. Preferably the conditions are so chosen to obtain a base oil grade comprising more than 95 wt% saturates and more preferably such that a base oil is obtained comprising more than 98 wt% saturates. The hydrofinishing step is suitably carried out in cascade with the dewaxing step.

The hydrofinishing step is suitably carried out at a temperature between 230 and 380 °C, a total pressure of between 10 to 250 bar and preferably above 100 bar and more preferably between 120 and 250 bar. The WHSV (Weight hourly space velocity) ranges from 0.3 to 2 kg of oil per litre of catalyst per hour (kg/l.h).

The hydrofinishing or hydrogenation catalyst is suitably a supported catalyst comprising a dispersed Group VIII metal. Possible Group VIII metals are cobalt, nickel, palladium and platinum. Cobalt and nickel containing catalysts may also comprise a Group VIB metal, suitably molybdenum and tungsten.

Suitable carrier or support materials are low acidity amorphous refractory oxides. Examples of suitable amorphous refractory oxides include inorganic oxides, such as alumina, silica, titania, zirconia, boria, silica-alumina, fluorided alumina, fluorided silica-alumina and mixtures of two or more of these.

Suitable hydrogenation catalysts include those catalysts comprising as one or more of nickel (Ni) and cobalt (Co) in an amount of from 1 to 25 percent by weight (wt%), preferably 2 to 15 wt%, calculated as element relative to total weight of catalyst and as the Group VIB metal component one or more of in an amount of from 5 to 30 wt%, preferably 10 to 25 wt%, calculated as element relative to total weight of catalyst. Examples of suitable nickel-molybdenum containing catalyst are KF-847 and KF-8010 (AKZO Nobel) M-8-24 and M-8-25 (BASF), and C-424, DN-190, HDS-3 and HDS-4 (Criterion). Examples of suitable nickel-tungsten containing catalysts are NI-4342 and NI-4352 (Engelhard), C-454 (Criterion). Examples of suitable cobalt-molybdenum containing catalysts are KF-330 (AKZO-Nobel), HDS-22 (Criterion) and HPC-601 (Engelhard).

For hydrocracked feeds containing low amount of sulphur, as in the present invention, preferably platinum containing and more preferably platinum and palladium containing catalysts are used. The total amount of these noble Group VIII metal component(s) present on the catalyst is suitably from 0.1 to 10 wt%, preferably 0.2 to 5 wt%, which weight percentage indicates the amount of metal (calculated as element) relative to total weight of catalyst.

Preferred supports for these palladium and/or platinum containing catalysts are amorphous silica-alumina, whereby more preferably the silica-alumina comprises from 2 to 75 wt% of alumina. Examples of suitable silica-alumina carriers are disclosed in WO-A-9410263. A preferred catalyst comprises an alloy of palladium and platinum preferably supported on an amorphous silica-alumina carrier of which the commercially available catalyst C-624 of Criterion Catalyst Company (Houston, TX) is an example.

After the topping step an optional further step is performed to improve the base oil stability by contacting the effluent of the hydrofinishing step with active carbon as for example described in EP-A-712922.

5       After the hydrofinishing step a low boiling fraction is preferably removed by means of distillation in order to obtain a product having the desired volatility properties.

10       The invention is also directed to a novel medium machine oil grade having a kinematic viscosity at 100 °C of between 11 and 12.5 cSt, a viscosity index of between 95 and 120, a sulphur content of below 100 ppmw and a saturates content of above 98 wt% obtainable by a process as described above. This base oil grade can be used in a  
15       lubricant composition comprising also one or more additives. The lubricant composition is suitably used as a 20W50 automotive lubricant or as a ISO 100 industrial formulation, for example as a hydraulic or turbine oil.

20       The process is illustrated in Figure 1. Figure 1 shows that a hydrocarbon mixture (1) is fed to a preliminary hydrotreater (2). The effluent (3) of hydrotreater (2) is fed to a hydrocracker step (4). The hydrotreater (2) and hydrocracker (4) may be combined in one vessel in a so-called stacked bed. The effluent or  
25       hydrocrackate (5) of the hydrocracker (4) is separated in distillation step (6) in one or more fuels fractions (7) and a bottoms or hydrowax fraction (8). The hydrowax (8) is further separated in vacuum distillation unit (9) into a heavy gas oil fraction (10), a vacuum gas oil  
30       fraction (11) and, as illustrated for distillation mode (d1), a spindle oil fraction (12), a medium machine oil fraction (14) and a first rest fraction (13) boiling between said spindle oil and medium machine oil fraction. The vacuum gas oil fraction can optionally also be  
35       further processed to a light grade base oil by performing

steps (a)-(c) of the process according to the present invention. In a blocked out mode the spindle oil fraction (12) (not shown) and the medium machine oil fraction (14) (as shown) are further processed, from storage tanks (12') and (14'), in catalytic dewaxing unit (15) yielding a dewaxed fraction (16), which fraction (16) is further processed in hydrofinishing unit (17). From the mixture (18) obtained in hydrofinishing unit (17) a low boiling fraction (20) is removed in distillation unit (19) thereby yielding the desired base oil grade (21). The total fuels make of this process comprises mixtures (7), (10), (11) and (20).

Figure 2 shows distillation mode (d2). In this mode the hydrowax (8) is further separated in vacuum distillation unit (9) into a heavy gas oil fraction (10), a vacuum gas oil fraction (11), a spindle oil fraction (12), a light machine oil fraction (22) and a second rest fraction (23) boiling above the light machine oil fraction. In a blocked out mode the spindle oil fraction (12) (not shown) and the light machine oil fraction (22) (as shown) are further processed, from storage tanks (12') and (22') to the respective base oil grade. All other references have the meaning as in Figure 1.

The invention will be illustrated by the following non-limiting examples. Examples 1-2 represent calculated results, wherein use has been made of hydrocracker models, plant data and experimental results. It is believed that these result give a good representation of how the process according to the invention will perform in reality.

#### Example 1 using a single mode vacuum distillation

To a distillation column a hydrowax containing residue is fed at a rate of 4883 ton feed per day (t/d). The feed has the properties as listed in Table 1.



Table 1

Feed	
boiling point at vol 5% (°C)	287
vK at 100 °C (cSt)	3.95
wax content (wt%)	18.2
sulphur (ppm)	24
nitrogen (ppm)	<1

The feed is separated in a vacuum distillation into  
 1042 t/d heavy gas oil, 1285 t/d vacuum gas oil, 591 t/d  
 of a rest fraction boiling between the spindle oil  
 fraction and the vacuum gas oil, 291 t/d of light machine  
 5 oil, 664 t/d of medium machine oil and 300 t/d of a  
 residue fraction. The spindle oil, light machine oil and  
 medium machine oil fractions were subsequently further  
 processes by means of catalytic dewaxing and hydro-  
 finishing in a blocked out mode. From the product ex  
 10 hydrofinishing the lower boiling fraction is removed  
 which totals on average for all base oil grades to  
 422 t/d. The process yields (on an average 350 day  
 runtime basis) 557 t/d spindle oil grade, 214 t/d light  
 machine oil and 471 t/d medium machine oil grade. The  
 15 yield of base oils (Spindle oil, light machine oil and  
 medium machine oil) on hydrowax containing residue is  
 about 25 wt%.

The quality of the base oil grades is as listed in  
 Table 2.

Table 2

	Spindle oil grade	light machine oil grade	medium machine oil grade
Viscosity at 100 °C (cSt) (1)	4.65	8.65	12.0
Viscosity Index (2)	106	103	100
Noack volatility (%) (3)	16.5	-	-
Pour Point (°C) (4)	-15	-12	-12
saturates (wt%) (5)	99.2	98.4	98.1

(1) according to ASTM D445; (2) according to ASTM D2270;

(3) according to CEC L-40-T-87; (4) according to ASTM D97;

(5) according to ASTM D207

Example 2 using two modes of distillation according the present invention

Example 1 is repeated with the same feed except that during 245 days of the total of 350 days on stream a hydrowax feed of 4109 t/d is separated in the vacuum distillation into 866 t/d heavy gas oil, 1153 t/d vacuum gas oil, 723 t/d of spindle oil, 416 t/d of a first rest fraction boiling between the spindle oil fraction and the medium machine oil fraction and 951 t/d of medium machine oil. The thus obtained spindle oil and medium machine oil fractions were subsequently further processes by means of catalytic dewaxing and hydrofinishing in a blocked out mode. From the product ex hydrofinishing the lower boiling fraction is removed. This distillation mode

yields (on an average yearly basis) 557 t/d spindle oil grade and 660 t/d medium machine oil grade.

During the remaining days on stream the hydrowax is separated in the vacuum distillation into 866 t/d heavy gas oil, 1153 t/d vacuum gas oil, 723 t/d of spindle oil, 1083 t/d of light machine oil fraction and 329 t/d in a second rest fraction boiling above the light machine oil fraction. The thus obtained spindle oil and light machine oil fractions were subsequently further processes by means of catalytic dewaxing and hydrofinishing in a blocked out mode. From the product ex hydrofinishing the lower boiling fraction is removed. This distillation mode yields (on an average 350 day runtime basis) 557 t/d spindle oil grade and 751 t/d light machine oil grade.

Both distillation modes thus yield (on an average yearly basis) 557 t/d spindle oil grade, 214 t/d light machine oil and 471 t/d medium machine oil grade. The yield of base oils (Spindle oil, light machine oil and medium machine oil) on hydrowax containing residue is about 30 wt%. The quality of the base oil grades is as in Table 2.

### Example 3

A hydrowax containing residue having the properties as listed in Table 1 was distilled and a light machine oil fraction was obtained having a kinematic viscosity at 100 °C of 7.24 cSt, an initial boiling point (5 vol% TBP) of 440 °C and a final boiling (95 vol% TBP) point of 550 °C. This light machine oil fraction was subsequently dewaxed by contacting the fraction with the same dealuminated- platinum loaded- ZSM-5/silica catalyst as used in Examples 11 and 12 of WO-A-0029511 in the presence of hydrogen at a temperature of 354 °C, an outlet pressure of 141 bar, a WHSV of 1.00 kg/l.hr and a hydrogen gas rate of 640 Nl/kg feed.

The effluent thus obtained was subsequently hydro-finished by contacting the effluent in the presence of freshly supplied hydrogen over a commercial PtPd on amorphous silica-alumina carrier (C-624 of Criterion Catalyst Company (Houston, TX)). The operating conditions were a hydrogen partial pressure of 129 bar, a WHSV of 1.0 kg/l/h, a recycle gas rate of 500 Nl/kg and a temperature of 260 °C.

Gaseous components were separated from the effluent of the hydrofinishing by vacuum flashing at a cutting temperature of 445 °C. A light fraction was subsequently separated by distillation after which the desired API Group II light machine oil grade was obtained having the properties as listed in Table 3.

Table 3

	API Group II light machine oil
saturates (wt%) (IP 391)	98.6
polars (wt%) (IP 391)	1.4
sulphur (mg/kg)	18
nitrogen (mg/kg)	<1
Viscosity Index	107
viscosity at 100 °C (cSt)	8.513
viscosity at 40 °C (cSt)	62.54
pour point (°C)	-12

C L A I M S

1. 1. Process to prepare a spindle oil, light machine oil and a medium machine oil base oil grade by
- (a) performing a separate catalytic dewaxing on a spindle oil fraction, a light machine oil fraction and a medium machine oil fraction as obtained in a vacuum distillation of a bottoms fraction of a fuels hydrocracking process;
- (b) performing a separate hydrofinishing of the light and medium machine oil fractions obtained in step (a);
- (c) separating the low boiling compounds from the spindle oil, light machine oil and medium machine oil fractions as obtained in step (a) and (b) and obtaining the spindle oil, light machine oil and medium machine oil base oil grade;
- (d) wherein the vacuum distillation is performed by alternately performing the distillation in two modes wherein the first mode (d1) the bottoms fraction is separated into a gas oil fraction, a spindle oil fraction, a medium machine oil fraction and a first rest fraction boiling between said spindle oil and medium machine oil fraction and in the second mode (d2) the bottoms fraction is separated into a gas oil fraction, a spindle oil fraction, a light machine oil fraction and a second rest fraction boiling above the light machine oil fraction.
2. Process according to claim 1, wherein the spindle oil grade has a kinematic viscosity at 100 °C of between 3.5 and 5.5 cSt and a Noack volatility of below 20% or a flash point of above 180 °C, the light machine oil grade has a kinematic viscosity at 100 °C of between 6.5 and 9 cSt and the medium machine oil grade has a kinematic viscosity at 100 °C of between 10 and 13.5 cSt.

3. Process according to claim 2, wherein the medium machine oil grade has a kinematic viscosity at 100 °C of between 11 and 12.5 cSt.
4. Process according to any one of claim 1, wherein the catalytic dewaxing in step (a) is performed by contacting the vacuum distillation fraction with hydrogen and a catalyst containing a molecular sieve such that the pour point is reduced by at least 10 °C.
5. Process according to claim 4, wherein the molecular sieve is ZSM-5, ZSM-12, ZSM-22, ZSM-23, SSZ-32, ZSM-35, ZSM-48 or SAPO-11.
6. Process according to claim 4, wherein the molecular sieve is an intermediate pore size zeolite and wherein the catalyst also comprises a binder and a Group VIII metal.
7. Process according to claim 6, wherein the binder is a low acidity refractory oxide binder material which is essentially free of alumina and wherein the surface of the intermediate pore size zeolite has been modified by subjecting the zeolite to a surface dealumination treatment.
8. Process to operate a fuels hydrocracker which hydrocracker yields a naphtha, kerosine, gas oil and a bottoms fraction, wherein the bottoms fraction contains more than 15 wt% of a fraction, which has a kinematic viscosity at 100 °C of above 9 cSt, and wherein the weight percentage is calculated on the total of compounds which boil above 370 °C in the bottoms fraction, by first (i) hydrotreating a hydrocarbon feed at a feed conversion of less than 30 wt% and (ii) hydrocracking the product of step (i) in the presence of a hydrocracking catalyst at such a conversion level that the overall conversion of step (i) and (ii) is between 55 and 80 wt%.
9. Process according to claim 8, wherein the conversion in hydrotreating step (i) is between 15 and 25 wt%.

10. Process according to any one of claims 8-9, wherein the overall conversion is between 60 and 75 wt%.
11. Process according to any one of claims 8-10, wherein the catalyst used in step (ii) comprises more than 1 wt% of an acidic large pore size zeolite, a porous support and a Group VIII/Group VIB metal combination.
12. Process according to any one of claims 1-7, wherein a bottoms fraction is used in step (d) as obtained from the process according to any one of claims 8-11.
13. Medium machine oil grade having a kinematic viscosity at 100 °C of between 11 and 12.5 cSt, a viscosity index of between 95 and 120, a sulphur content of below 100 ppmw and a saturates content of above 98 wt% obtainable by a process according to any one of claims 8-12.
14. Lubricant composition comprising an additive and a base oil as obtained by a process according to any one of claims 8-12.
15. Use of the lubricant comprising a medium machine oil of claim 13 as a 20W50 automotive lubricant or as a ISO 100 industrial formulation.

Fig.1.





Fig.2.





(19) World Intellectual Property Organization  
International Bureau



(43) International Publication Date  
27 June 2002 (27.06.2002)

PCT

(10) International Publication Number  
**WO 02/050213 A3**

(51) International Patent Classification<sup>7</sup>: **C10G 65/12**,  
C10M 101/02, 171/02

Kevin, John, Anthony [NL/FR]; Route Départemental  
no. 3, F-76650 Petit Couronne (FR).

(21) International Application Number: PCT/EP01/15134

(22) International Filing Date:  
18 December 2001 (18.12.2001)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
00403588.7 19 December 2000 (19.12.2000) EP

(71) Applicant (for all designated States except US): **SHELL  
INTERNATIONALE RESEARCH MAATSCHAPPIJ  
B.V.** [NL/NL]; Carel van Bylandtlaan 30, NL-2596 HR  
The Hague (NL).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU,  
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,  
CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,  
GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,  
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,  
MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG,  
SI, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ,  
VN, YU, ZA, ZM, ZW.

(84) Designated States (*regional*): ARIPO patent (GH, GM,  
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),  
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),  
European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR,  
GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent  
(BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR,  
NE, SN, TD, TG).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **VAN BEIJNUM**,  
**Johannes** [NL/NL]; Badhuisweg 3, NL-1031 CM  
Amsterdam (NL). **GEUKEMA, Arjen, Peter** [NL/NL];  
Badhuisweg 3, NL-1031 CM Amsterdam (NL). **POLDER**,



Published:

— with international search report

(88) Date of publication of the international search report:  
20 March 2003

[Continued on next page]

(54) Title: PROCESS TO PREPARE A SPINDLE OIL, LIGHT MACHINE OIL AND A MEDIUM MACHINE OIL



(57) Abstract: Process to prepare a spindle oil, light machine oil and a medium machine oil base oil grade by (a) performing a separate catalytic dewaxing on a spindle oil fraction, a light machine oil fraction and a medium machine oil fraction as obtained in a vacuum distillation of a bottoms fraction of a fuels hydrocracking process; (b) performing a separate hydrofinishing of the light and medium machine oil fractions obtained in step (a); (c) separating the low boiling compounds from the spindle oil, light machine oil and medium machine oil fractions as obtained in step (a) and (b) and obtaining the spindle oil, light machine oil and medium machine oil base oil grade; (e) wherein the vacuum distillation is performed by alternately performing the distillation in two modes wherein the first mode (d1) the bottoms fraction is separated into a gas oil fraction, a spindle oil fraction, a medium machine oil fraction and a first rest fraction boiling between said spindle oil and medium machine oil fraction and in the second mode (d2) the bottoms fraction is separated into a gas oil fraction, a spindle oil fraction, a light machine oil fraction and a second rest fraction boiling above the light machine oil fraction.



---

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

## A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 C10G65/12 C10M101/02 C10M171/02

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 C10G C10M

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data, PAJ

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	WO 97 18278 A (MOBIL OIL CORP) 22 May 1997 (1997-05-22) cited in the application claims 1,5,10,17,19; figures 1,2 page 7, line 14-34 page 8, line 23 -page 9, line 4 page 13, line 15-23 page 13, line 35 -page 16, line 6 page 19, line 4 -page 20, line 16	1-7, 12
X	claim 3; example 1; table 4 page 16, line 20-26 page 18, line 20-24 --- -/--	8-11



Further documents are listed in the continuation of box C.



Patent family members are listed in annex.

## \* Special categories of cited documents:

- \*A\* document defining the general state of the art which is not considered to be of particular relevance
- \*E\* earlier document but published on or after the international filing date
- \*L\* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- \*O\* document referring to an oral disclosure, use, exhibition or other means
- \*P\* document published prior to the international filing date but later than the priority date claimed

- \*T\* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- \*X\* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- \*Y\* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- \*Z\* document member of the same patent family

Date of the actual completion of the international search

2 September 2002

Date of mailing of the international search report

2 09.02

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax: (+31-70) 340-3016

Authorized officer

Harf, J

## C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	WO 94 26848 A (YUKONG LTD) 24 November 1994 (1994-11-24) cited in the application claims 1,2,6,7; figure 2A; examples 1,2; table 2A page 3, line 1-5 page 5, line 15-31	1-7,12
A	table 1 page 1, line 36 -page 2, line 2	8-11
A	EP 0 590 673 A (MITSUBISHI OIL CO) 6 April 1994 (1994-04-06) claim 1 page 2, line 56 -page 3, line 19	1-7,12
A	example 1 page 4, line 7-13	8-11

# INTERNATIONAL SEARCH REPORT

International application No.  
PCT/EP 01/15134

## Box I Observations where certain claims were found unsearchable (Continuation of item 1 of first sheet)

This International Search Report has not been established in respect of certain claims under Article 17(2)(a) for the following reasons:

1. ☐ Claims Nos.:  
because they relate to subject matter not required to be searched by this Authority, namely:
2. ☐ Claims Nos.:  
because they relate to parts of the International Application that do not comply with the prescribed requirements to such an extent that no meaningful International Search can be carried out, specifically:
3. ☐ Claims Nos.:  
because they are dependent claims and are not drafted in accordance with the second and third sentences of Rule 6.4(a).

## Box II Observations where unity of invention is lacking (Continuation of item 2 of first sheet)

This International Searching Authority found multiple inventions in this International application, as follows:

see additional sheet

1. ☐ As all required additional search fees were timely paid by the applicant, this International Search Report covers all searchable claims.
2. ☐ As all searchable claims could be searched without effort justifying an additional fee, this Authority did not invite payment of any additional fee.
3. ☒ As only some of the required additional search fees were timely paid by the applicant, this International Search Report covers only those claims for which fees were paid, specifically claims Nos.:  
1-12
4. ☐ No required additional search fees were timely paid by the applicant. Consequently, this International Search Report is restricted to the invention first mentioned in the claims; it is covered by claims Nos.:

Remark on Protest

- ☐ The additional search fees were accompanied by the applicant's protest.
- ☒ No protest accompanied the payment of additional search fees.

## FURTHER INFORMATION CONTINUED FROM PCT/ISA/ 210

This International Searching Authority found multiple (groups of) inventions in this international application, as follows:

1. Claims: 1-7 and 12

process to prepare a spindle oil, light and medium machine oil, three base oil grades defined by their viscosity ranges, by fuels hydrocracking possibly preceded by a hydrotreatment of the feed, vacuum distillation of a hydrocrackate bottoms fraction in two alternating modes to yield a spindle oil and a medium machine oil in the first mode as well as yield a spindle oil and a light machine oil in the second mode, separate catalytic dewaxing of the three base oil fractions, separate hydrofinishing of the light and medium machine oil and separation of low boiling compounds from the three base oil fractions

2. Claims: 8-11

process to operate a fuels hydrocracker to yield a naphtha, kerosene, gas oil and a specific bottoms fraction by hydrotreating the feed and catalytically hydrocracking the hydrotreated feed with an overall conversion between 55 and 80 wt%

3. Claim : 13 and 15

medium machine oil grade defined by its viscosity, sulfur content and saturates content as well as use of this medium machine oil as a lubricant

4. Claim : 14

lubricant composition comprising a base oil and an additive

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
WO 9718278	A	22-05-1997	AU 715730 B2	10-02-2000
			AU 6907196 A	05-06-1997
			EP 0863963 A1	16-09-1998
			JP 2002502436 T	22-01-2002
			WO 9718278 A1	22-05-1997
WO 9426848	A	24-11-1994	KR 9613606 B1	09-10-1996
			AT 176799 T	15-03-1999
			AU 685808 B2	29-01-1998
			AU 6761094 A	12-12-1994
			BR 9406721 A	06-02-1996
			CA 2162130 A1	24-11-1994
			CN 1123037 A ,B	22-05-1996
			DE 69416585 D1	25-03-1999
			DE 69416585 T2	15-07-1999
			EP 0699225 A1	06-03-1996
			JP 2697749 B2	14-01-1998
			JP 8510284 T	29-10-1996
			WO 9426848 A1	24-11-1994
			RU 2104294 C1	10-02-1998
			US 5580442 A	03-12-1996
EP 0590673	A	06-04-1994	JP 3057125 B2	26-06-2000
			JP 6116572 A	26-04-1994
			AU 662247 B2	24-08-1995
			AU 4876793 A	14-04-1994
			CA 2107376 A1	03-04-1994
			EP 0590673 A1	06-04-1994
			KR 191688 B1	15-06-1999
			SG 48976 A1	18-05-1998
			US 5460713 A	24-10-1995